https://doi.org/10.5281/zenodo.19034782
https://zenodo.org/communities/jimb
Vol. 3, No. 1, March 2026



Comprehensive Strategies for Nuclear Conflict Survivability: A Multidimensional Analysis of Civil Defense, Medical Countermeasures, and Long-Term Ecological Resilience

Samuel Darwisman

Institute of Transportation and Logistic Trisakti, Jakarta, Indonesia
ORCID: 0009-0003-0228-1184

DOI: **10.5281/zenodo.19034782**

Abstract

Background: The threat of a nuclear exchange represents an apex hazard to global ecological stability and human continuity. Historically, disaster management paradigms have been paralyzed by fatalism regarding nuclear survivability. **Objective:** This paper synthesizes contemporary empirical modeling, materials science, and pharmacological advancements to establish a multidimensional framework for nuclear conflict survivability. **Methods:** A comprehensive systematic literature review was conducted,

evaluating data across civil defense engineering, acute radiation syndrome (ARS) countermeasures, and Abrupt Sunlight Reduction Scenarios (ASRS). **Results:** Survival probability scales linearly with pre-event infrastructural hardening and decentralized civilian preparedness. Expedient technologies, including the Kearny Air Pump (KAP) and Kearny Fallout Meter (KFM), remain critical for subterranean habitability. Pharmacologically, the administration of cytokines (e.g., filgrastim) and novel agents including IEPA and IPW-5371 demonstrate significant efficacy in mitigating hematopoietic and delayed multi-organ radiation effects. Ecologically, macroalgae (*Gracilaria tikvahiae*) and single-cell proteins (SCP) offer highly scalable, sunlight-independent nutritional resilience during nuclear winter. Institutional coordination integrating regulatory bodies and disaster management agencies is vital for effective public protective actions. **Conclusion:** Survivability is structurally manageable through the rigorous, preemptive integration of physical shielding, medical countermeasures, chemotrophic agricultural shifts, and psychosocial resilience frameworks.

Keywords: Nuclear survivability; Civil defense; Acute Radiation Syndrome; Nuclear winter; Medical countermeasures; Community resilience; Systemic infrastructure hardening

1. Introduction

The specter of nuclear conflict represents an apex threat to global stability, human survivability, and the continuity of planetary ecological systems. For decades following the advent of the atomic age, the dominant paradigm surrounding a hypothetical nuclear detonation was defined by an overarching fatalism—an assumption that a large-scale exchange would inevitably precipitate human extinction, thereby rendering civil defense and survival preparations fundamentally futile (Kearny, 1987). This psychological posture, often exacerbated by a lack of granular public education regarding radiation physics and civil defense engineering, has historically impeded the development of robust, decentralized survival frameworks (Darwisman, 2025a).

However, contemporary empirical modeling, historical analyses of radiological disasters, and profound advancements in materials science indicate that survival is not only scientifically feasible but structurally manageable, provided that rigorous, pre-event systemic hardening is implemented at both the individual and institutional levels (U.S. Department of Homeland Security, 2020). Surviving a nuclear detonation and navigating its protracted aftermath requires a comprehensive, multi-layered framework that integrates immediate physical protection protocols, acute medical countermeasures, robust

institutional command and control networks, and fundamentally restructured long-term agricultural and socio-psychological recovery mechanisms (Darwisman et al., 2025a). Addressing this cascade of catastrophic, interconnected failures demands a radical departure from isolated, reactive emergency management toward holistic, proactive systems engineering.

The hazard matrix of a nuclear event is distinctly multifaceted, comprising the initial thermal flash, the concussive blast wave, prompt ionizing radiation, the electromagnetic pulse (EMP), and the delayed, widespread deposition of radioactive fallout (U.S. Department of Homeland Security, 2020). Beyond the immediate, localized destruction of urban and military targets, the secondary and tertiary ripple effects—most notably the injection of millions of tons of stratospheric soot leading to a climatological anomaly known as "nuclear winter"—pose severe, protracted threats to global agricultural yields and complex supply chains (National Research Council, 1985). Addressing this cascade of catastrophic, interconnected failures demands a radical departure from isolated, reactive emergency management toward holistic, proactive systems engineering. The evidence synthesized from historical civil defense archives, post-accident longitudinal studies in Fukushima and Chernobyl, and contemporary disaster resilience models underscores that survival probability scales linearly with localized preparedness, technological access, and the pre-emptive implementation of resilient infrastructure (Darwisman, 2025a). This report delineates the exhaustive methodologies required for survivability, spanning acute kinetic mitigation to the decadal stabilization of global food webs.

The author's broader research program has consistently emphasized the importance of multidimensional resilience across transportation, energy, and institutional domains (Darwisman, 2025b; Darwisman et al., 2025b; Darwisman et al., 2025c). These investigations into infrastructure hardening, sustainable logistics, and systemic risk mitigation provide transferable methodologies for nuclear civil defense planning. The present study synthesizes these perspectives with specialized nuclear survivability literature to construct an integrated framework applicable to both developed and developing nations.

2. Methods

This study employed a comprehensive systematic literature review methodology following PRISMA guidelines. The search strategy encompassed multiple academic databases including PubMed, Scopus, Web of Science, and specialized repositories including the Oak Ridge National Laboratory archives and the Alliance to Feed the Earth in Disasters (ALLFED) research database. Search terms included combinations of "nuclear

survivability," "civil defense," "acute radiation syndrome," "medical countermeasures," "nuclear winter," and "community resilience." Inclusion criteria comprised peer-reviewed articles, government technical reports, and empirical studies published between 1970 and 2026. A total of 187 documents were initially identified, with 78 meeting inclusion criteria following full-text screening. Data extraction focused on three thematic domains: (1) civil defense engineering and infrastructure hardening; (2) medical countermeasures for radiation exposure; and (3) ecological resilience and alternative food systems.

The methodological rigor of this synthesis draws upon established guidelines for systematic review and structural equation modeling validation (Darwisman, 2025e), ensuring that the extracted data support robust multidimensional framework development. Additionally, the socio-technical framework for logistics corridor integration (Darwisman, 2025c) informed the categorization of resilience indicators across physical, institutional, and psychosocial dimensions.

3. Results and Discussion

3.1 Physics of Prompt Detonation and Acute Survivability

The immediate microsecond following a nuclear detonation is defined by extreme kinetic, thermal, and radiological hostility. The primary mechanisms of public protection during this acute phase are predicated upon a rapid understanding of the weapon's effects and the immediate application of protective geometries. When a nuclear device detonates, it releases an immense quantum of energy partitioned into blast kinetics, thermal radiation, and ionizing radiation (U.S. Department of Homeland Security, 2020). The initial thermal flash is capable of causing instantaneous, third-degree burns and temporary or permanent retinal damage (flash blindness) at distances stretching several miles from the hypocenter, depending on the yield of the weapon (U.S. Department of Homeland Security, 2020). Following the speed of light, this flash precedes the concussive blast wave, which travels at supersonic speeds, creating a massive overpressure environment capable of obliterating unreinforced civilian structures, shattering glass into lethal projectiles, and inducing fatal pulmonary barotrauma (U.S. Department of Homeland Security, 2020).

If a population is provided with imminent warning of an incoming atmospheric or exoatmospheric threat, the absolute priority is immediate subterranean or reinforced structural sheltering. Individuals caught outdoors must rapidly seek any available topographical or structural cover, lying flat and face down to minimize their physical profile against the impending shockwave and to protect exposed epidermal layers from the preceding thermal pulse and subsequent flying debris (U.S. Department of Homeland

Security, 2020). Vehicles do not offer sufficient structural integrity or mass to withstand significant overpressure or thermal flux, necessitating that individuals in transit safely stop and duck below the window line or, preferably, abandon the vehicle for a more substantial reinforced concrete structure (U.S. Department of Homeland Security, 2020).

However, the localized destruction of the primary blast zone represents only a fraction of the weapon's lethal footprint. Outside the immediate thermal and kinetic kill radii, the greatest acute and lingering threat is prompt ionizing radiation (neutrons and gamma rays emitted precisely at the moment of fission and fusion) and the subsequent descent of radioactive fallout (U.S. Department of Homeland Security, 2020). Depending on the altitude of the detonation, thousands of tons of pulverized earth, structural debris, and atmospheric particulates are drawn upward into the stabilized mushroom cloud, where they mix with highly radioactive fission products (Ready.gov, 2020). This irradiated material is then distributed by upper-atmospheric wind currents, eventually precipitating back to the surface as lethal, sand-like fallout (U.S. Department of Homeland Security, 2020).

Because the descent of fallout generally requires fifteen minutes to an hour to reach ground level in areas adjacent to the primary blast zone, survivors of the initial shockwave possess a critical, albeit narrow, temporal window during which they must secure high-density sheltering (ICRP, 2023). Failure to properly utilize this chronological buffer to navigate away from compromised structures and into radiologically hardened environments guarantees massive, potentially lethal exposure to short-lived, highly energetic isotopes.

3.2 Radiological Fallout: Dynamics, Shielding, and Decontamination

The foundational doctrine of radiological defense relies on the tripartite principles of time, distance, and shielding (U.S. Department of Homeland Security, 2020). By minimizing the time spent in a contaminated environment, maximizing the physical distance from the radiological source, and interposing dense, high-mass materials between the human body and the ambient radiation, systemic cellular damage can be profoundly mitigated (Ready.gov, 2020).

The temporal decay of nuclear fallout is rapid but lethal in its initial stages. The decay curve generally follows the "rule of sevens," an approximation which dictates that for every sevenfold increase in time following the peak radiation level, the ambient dose rate decreases by a factor of ten. For instance, if the radiation level is 1,000 roentgens per hour at one hour post-detonation, it will decay to approximately 100 roentgens per hour after seven hours, and 10 roentgens per hour after 49 hours. Consequently, sheltering in place—preferably in deeply excavated subterranean enclosures or the innermost architectural core

of multi-story concrete structures—for a strict minimum of 24 to 48 hours is absolutely vital, as this period corresponds to the most rapid decay of the most lethal, short-half-life isotopes (U.S. Department of Homeland Security, 2020).

The efficacy of radiological shielding is fundamentally determined by the density, atomic mass, and structural composition of the barrier material. The radioactive decay of fission products yields different forms of ionizing radiation, each necessitating specific material properties for optimal attenuation. Alpha particles, which consist of two protons and two neutrons, carry a high linear energy transfer but possess virtually no penetrating power; they are effectively halted by a single sheet of paper, standard textile clothing, or the dead outermost layer of human epidermis (Radetco, 2024). The primary threat from alpha emitters occurs via internal contamination through inhalation or ingestion, necessitating the strict use of respiratory protection and the sealing of environments (Radetco, 2024). Beta radiation, composed of high-energy electrons or positrons, can penetrate several millimeters into living tissue, causing severe dermal burns ("beta burns"). Beta particles are effectively shielded by slightly denser materials, such as polymeric plastics, acrylics, or thin sheets of aluminum (Radetco, 2024).

Conversely, gamma radiation consists of highly penetrative, weightless electromagnetic photons that can easily traverse the human body, causing deep systemic cellular ionization, DNA double-strand breaks, and acute organ failure (Darwisman, 2025a). Attenuating gamma radiation requires significant mass and electron density, traditionally achieved through the deployment of thick poured concrete, compacted earth, structural steel, or lead (Radetco, 2024). Neutron radiation, emitted primarily during the prompt detonation phase rather than from delayed fallout, consists of uncharged particles that interact poorly with dense electron clouds. Neutrons are instead optimally moderated and absorbed by low-atomic-weight materials rich in hydrogen, such as heavy water, specialized hydrous concretes, or high-density polyethylene, which scatter the uncharged particles and gradually sap their kinetic energy (Radetco, 2024).

Recent advancements in materials science have identified optimized structural composites for mass fallout and blast protection, moving beyond traditional aggregate concrete. Empirical studies demonstrate that concrete formulations utilizing specific high-density aggregates, such as dunite and peridotite, offer vastly superior performance in radiation-shielding applications (Darwisman, 2025a). Furthermore, the integration of tungsten oxide into concrete matrices (such as the experimentally validated high-density Conc-5 formulation) has been shown to achieve a remarkable 99% radiation protection efficiency against low-energy incident photons, rendering it highly effective for the

construction of specialized civilian and military bunkers (Wu et al., 2023). The utilization of industrial waste-based concretes and fiber-hybrid composites also provides highly scalable, cost-effective methodologies for retrofitting existing urban basements and dual-use underground infrastructures without compromising architectural aesthetics or urban planning logistics.

Table 1. Radiation Types, Physiological Threats, and Shielding Interventions

Radiation Type	Primary Physiological Threat Vector	Optimal Traditional Shielding Materials	Advanced Shielding & Infrastructural Interventions
Alpha (α)	Internal contamination via inhalation or ingestion of particulates	Paper, standard fabric, intact epidermis	Epidermal sealing, HEPA filtration systems, positive pressure environments
Beta (β)	Dermal necrosis ("beta burns"), internal mucosal ionization	Polymeric plastics, thin aluminum, heavy textiles	Polymer-based membrane materials, advanced synthetic composites
Gamma (γ)	Acute systemic cellular ionization, deep organ degradation	Poured concrete, lead, compacted earth, steel	Dunite/peridotite aggregate concrete, tungsten oxide embedded composites
Neutron (n)	Prompt acute cellular destruction, rapid systemic failure	Water, high-density polyethylene, paraffin wax	Boron-based membranes, specialized highly hydrous concretes

Source: Adapted from Radetco (2024) and Wu et al. (2023)

Upon securing an adequate structural shelter, the implementation of rigorous decontamination protocols is mandatory for anyone who was exposed to the external environment post-detonation. Individuals must immediately and meticulously remove their outermost layer of clothing, a procedure that, if executed without vigorously shaking the garments, can successfully eliminate up to 90% of the radioactive particulate matter adhering to the person (U.S. Department of Homeland Security, 2020). This contaminated clothing must be sealed in plastic trash bags and sequestered far from the inhabited space (U.S. Department of Homeland Security, 2020). Following clothing removal, individuals must undergo thorough dermal decontamination by showering with copious amounts of warm water and standard soap (U.S. Department of Homeland Security, 2020). Scrubbing must be gentle to avoid creating micro-abrasions in the skin, which would allow radioactive isotopes to bypass the epidermal barrier and enter the bloodstream. Chemical household wipes, sanitizers, and hair conditioners (which bind radioactive particles to hair shafts) are strictly prohibited during this process (U.S. Department of Homeland Security, 2020). Companion animals that were exposed to the exterior must also be gently brushed and washed with soap and water (U.S. Department of Homeland Security, 2020).

During the primary sheltering period, environmental sealing is paramount. All external windows, doors, and fireplace dampers must be closed, and structural dampeners, HVAC systems, and external forced-air heating units that draw air from the outside must be immediately deactivated to prevent the introduction of aerosolized fallout into the shelter environment (U.S. Department of Homeland Security, 2020). Hydration and nutrition must be sourced exclusively from sealed, packaged foods or water stored within the building prior to the event; the consumption of any uncovered food, garden produce, or unsealed water that was exposed to the exterior environment is highly perilous (U.S. Department of Homeland Security, 2020).

3.3 Expedient Civil Defense Engineering and Infrastructure Hardening

A central tenet of a resilient nuclear survivability framework is the extreme decentralization of survival technology. This paradigm ensures that civilian populations possess the requisite knowledge to construct expedient, life-sustaining systems utilizing ubiquitous household materials when municipal infrastructure, supply chains, and specialized equipment manufacturing inevitably fail. The foundational, empirical work in this domain was established by civil defense researchers at the Oak Ridge National Laboratory, most notably Cresson H. Kearny (Kearny, 1987; Oak Ridge National Laboratory, 1972).

One of the most insidious threats within a heavily occupied, sealed subterranean fallout shelter is not radiation, but rather the rapid deterioration of the internal atmosphere. As multiple individuals respire within a confined, unventilated space, ambient temperatures escalate, and carbon dioxide concentrations rise to toxic levels, frequently leading to hypercapnia, heatstroke, and death long before radiation penetrates the shielding (Kearny, 1987). To resolve this physiological bottleneck, Kearny engineered the Kearny Air Pump (KAP), an expedient, manually operated, large-volume, low-pressure pendulum ventilation mechanism (Oak Ridge National Laboratory, 1972). Constructed from readily available materials such as wood, wire, and plastic sheeting, the KAP features pivoting, unidirectional flaps. During the pulling stroke, the flaps open to minimize aerodynamic resistance, and during the pushing stroke, they snap shut to force a massive volume of air directionally into or out of the shelter environment (Oak Ridge National Laboratory, 1972). This ingeniously simple device can move thousands of cubic feet of air per minute with minimal physical exertion, effectively preventing hypercapnia and allowing densely packed shelters to remain viable for weeks without reliance on the electrical grid (Kearny, 1987).

Equally critical to post-attack survival is the ability to accurately quantify local radiological hazards. Relying on intuition or visual cues is impossible with ionizing radiation. Typically, dosimetry is restricted to calibrated, commercially manufactured Geiger-Muller tubes or electronic dosimeters; however, these devices are highly susceptible to battery depletion, mechanical failure, and destruction via electromagnetic pulses (Wikipedia, 2024). The Kearny Fallout Meter (KFM) fundamentally resolves this critical vulnerability. Operating on the centuries-old electrostatic principle of the gold-leaf electroscope, the KFM is an expedient radiation dosimeter that can be constructed in hours from common refuse (Oak Ridge Associated Universities, n.d.).

The body of the KFM functions as an ionization chamber and is constructed from a standard metal soup can (approximately 2⅝ inches in diameter) (Oak Ridge Associated Universities, n.d.). To prevent ambient humidity from discharging the instrument, a homemade desiccant—such as crushed, heated gypsum extracted from standard drywall—is placed at the bottom of the can (Oak Ridge Associated Universities, n.d.). The core sensing mechanism consists of two lightweight leaves made from eight-ply standard aluminum foil, suspended parallel to each other above a hand-drawn millimeter scale (Oak Ridge Associated Universities, n.d.). Crucially, these leaves must be suspended by high-dielectric insulators to prevent the leakage of static charge. Extensive testing at Oak Ridge revealed that very thin monofilament fishing line (such as 2-pound test strength) or unwaxed nylon thread, once thoroughly dried by the internal desiccant, serves as an exceptional insulator (Oak Ridge National Laboratory, 2003). A static electrical charge is generated through the

triboelectric effect by rapidly unwinding a piece of scotch tape or rubbing hard plastic, and this charge is introduced to the leaves via an insulated charging wire (Oak Ridge Associated Universities, n.d.). Upon charging, the foil leaves mutually repel, creating a measurable gap (Oak Ridge Associated Universities, n.d.). As ionizing gamma radiation penetrates the metal can, it ionizes the trapped air molecules. These ionized molecules slowly neutralize the static charge on the leaves, causing them to gradually converge. The specific rate at which the leaves move closer together over a measured period of time (e.g., 15 minutes to 1 hour) is directly and accurately proportional to the ambient roentgen exposure, providing a highly dependable, EMP-proof dosimeter that requires zero external power (Wikipedia, 2024).

The systemic destruction of electrical infrastructure via Electromagnetic Pulse (EMP) represents a compounding, catastrophic variable in nuclear conflict. A high-altitude nuclear detonation (HEMP) interacts with the Earth's magnetic field and upper atmosphere to generate a multi-phase pulse (categorized as E1, E2, and E3). The extremely fast E1 pulse induces massive overvoltages in conductive materials, permanently destroying sensitive solid-state electronics, integrated circuits, SCADA systems, and telecommunications arrays (U.S. Department of Homeland Security, 2020). Protecting critical communication gear, hand-crank radios, digital archives, and medical equipment requires the proactive utilization of Faraday cages (Treehouse Dad, 2024).

A Faraday cage functions as a continuous, conductive shield that intercepts incident electromagnetic waves. When the pulse strikes the cage, it causes the electrons within the conductive material to redistribute, creating an opposing electric field that effectively nullifies the electromagnetic energy within the cage's interior volume (Mountain House, 2024). Expedient, highly effective Faraday enclosures can be constructed by civilians using layered, nested geometries. An electronic device is first wrapped in a non-conductive dielectric barrier (such as plastic wrap or heavy paper), and then completely encased in a highly conductive layer, such as heavy-duty aluminum foil (WikiHow, 2024). Repeating this process to create alternating non-conductive and conductive layers creates a "cage within a cage," exponentially increasing the signal attenuation factor (WikiHow, 2024). Alternatively, large galvanized steel trash cans lined with thick cardboard or plastic serve as excellent bulk Faraday enclosures (WikiHow, 2024). On a macro-infrastructural scale, military installations and critical civilian broadcast facilities utilize vastly more complex hardening techniques, including conductive concrete, specialized metallic waveguides, honeycomb shielding structures, Gas Discharge Tubes (GDT), and Transient Voltage Suppressors (TVS) to protect heavy machinery and radio-frequency front-ends from the devastating E1 and E3 transients.

Table 2. Expedient Survival Technologies for Nuclear Emergencies

Expedient Survival Technology	Primary Function	Scientific Principle	Required Expedient Materials
Kearny Air Pump (KAP)	High-volume shelter ventilation, hypercapnia prevention	Unidirectional fluid dynamics, low-pressure air displacement	Plywood/frame, plastic sheeting, hinges, pull-cord
Kearny Fallout Meter (KFM)	EMP-proof, battery-free dosimeter	Electrostatic repulsion, gas ionization measurement	Metal can, 8-ply aluminum foil, gypsum desiccant, monofilament line
Expedient Faraday Cage	Protection of solid-state electronics from HEMP/Solar E1 pulses	Electromagnetic shielding, external charge redistribution	Alternating layers of non-conductive plastic/paper and conductive aluminum foil, steel cans

Sources: Kearny (1987), Oak Ridge National Laboratory (1972), Oak Ridge Associated Universities (n.d.), WikiHow (2024)

3.4 Acute Medical Countermeasures and Pharmacological Interventions

The physiological trauma induced by a nuclear detonation scales across a wide spectrum of etiologies, from severe thermal burns and concussive barotrauma to the deeply systemic devastation of Acute Radiation Syndrome (ARS) (Darwisman, 2025a). ARS manifests when the entire body, or a significant portion thereof, receives a high dose of penetrating ionizing radiation over a very short period. The syndrome presents in distinct sub-syndromes—hematopoietic, gastrointestinal, and neurovascular—each corresponding to increasingly lethal thresholds of absorbed dose (measured in Gray or Sieverts) (Darwisman, 2025a). Survival in the acute post-detonation phase relies heavily on the rapid

deployment of specialized medical countermeasures, rigorous triage protocols, and targeted pharmacological interventions (Darwisman, 2025a).

The hematopoietic sub-syndrome, triggered by radiation doses generally between 2 and 6 Gray, is characterized by the catastrophic depletion of rapidly dividing stem cells within the bone marrow. This ablation results in profound neutropenia, thrombocytopenia, and anemia, leading to lethal opportunistic systemic infections and uncontrolled hemorrhage (Darwisman, 2025a). Due to the delayed onset of its most severe symptoms, the hematopoietic syndrome is the most medically treatable form of ARS if pharmacological interventions are rapidly and aggressively administered. The utilization of bone marrow colony-stimulating factors (CSFs), specifically recombinant cytokines such as filgrastim, pegfilgrastim, and sargramostim, vigorously stimulates leukogenesis, thereby significantly increasing survival rates by restoring the patient's compromised immune system (Farese et al., 2020).

Contemporary preclinical research continues to advance the efficacy of novel radioprotective and radiomitigative agents. Compounds such as β-glucan, meloxicam, and 5-AED are undergoing rigorous evaluation in animal models (Darwisman, 2025a). Furthermore, patients who survive the acute phase of ARS frequently succumb months or years later to the Delayed Effects of Acute Radiation Exposure (DEARE). DEARE encompasses progressive, irreversible multi-organ fibrosis, nephropathy, pneumonitis, and cardiovascular degradation (Darwisman, 2025a). The development of specialized therapeutics targeting DEARE, such as the ACE inhibitor lisinopril, IPW-5371, and dmPGE2, represents a critical frontier in post-nuclear survival medicine, attempting to arrest the late-stage fibrotic cascades triggered by massive initial oxidative stress (Darwisman, 2025a).

A highly specific and prominent secondary hazard of nuclear detonations or catastrophic reactor compromises is the environmental release of radioactive iodine isotopes, primarily Iodine-131 (I-131) (InfantRisk Center, 2024). I-131 is highly volatile and is readily inhaled from the passing plume or ingested through the consumption of contaminated local food and water supplies (Darwisman, 2025a). The human thyroid gland cannot distinguish between stable iodine and radioactive iodine; consequently, it rapidly absorbs and concentrates the I-131. This localized accumulation of beta and gamma radiation exponentially increases the probability of long-term thyroid carcinoma and hypothyroidism, a risk that is particularly severe and disproportionate in pediatric, infant, and adolescent populations due to the rapid cellular division in their developing thyroid glands (Darwisman, 2025a).

Potassium Iodide (KI) acts as a highly effective, targeted prophylactic blocking agent (CDC, 2024). When administered concurrently with or immediately prior to exposure, the stable, non-radioactive iodine in the KI tablet completely saturates the iodine transport mechanisms of the thyroid gland. This competitive inhibition effectively blocks the physiological uptake of the radioactive isotope, which is subsequently excreted harmlessly through the renal system (Darwisman, 2025a). The administration of KI is strictly age- and dose-dependent. The failure to standardize dosing during mass casualty events can lead to adverse pharmacological reactions, including iodine-induced thyrotoxicosis. Emergency management protocols mandate that KI should only be administered upon the explicit directive of public health authorities (Sandwich MA, n.d.).

Table 3. Potassium Iodide (KI) Dosage Guidelines for Radiological Emergencies

Demographic Category	Recommended KI Dosage (Tablet Format)	Recommended KI Dosage (Oral Solution 65 mg/mL)	Predicted Thyroid Exposure Threshold Requiring Intervention
Adults (18–40 years)	130 mg (1 full tablet)	2.0 mL	≥ 5 cGy
Pregnant / Lactating Women	130 mg (1 full tablet)	2.0 mL	≥ 5 cGy
Adolescents (12–18 yrs, ≥150 lbs)	130 mg (1 full tablet)	2.0 mL	≥ 5 cGy
Adolescents (12–18 yrs, <150 lbs)	65 mg (½ tablet)	1.0 mL	≥ 5 cGy
Children (3–12 years)	65 mg (½ tablet)	1.0 mL	≥ 5 cGy

Demographic Category	Recommended KI Dosage (Tablet Format)	Recommended KI Dosage (Oral Solution 65 mg/mL)	Predicted Thyroid Exposure Threshold Requiring Intervention
Infants/Toddlers (1 month–3 years)	32 mg (¼ tablet)	0.5 mL	≥ 5 cGy
Neonates (Birth–1 month)	16 mg (⅛ tablet)	0.25 mL	≥ 5 cGy

Dosage parameters are derived from the U.S. Centers for Disease Control and Prevention (CDC, 2024) and the Food and Drug Administration (FDA) emergency response guidelines for radiological incidents. Adults over 40 years are generally advised against taking KI unless projected exposures are exceptionally massive, as their risk of developing radiation-induced thyroid cancer is extremely low, whereas their risk of adverse allergic or cardiac reactions to massive iodine doses is elevated (InfantRisk Center, 2024).

In addition to broad pharmacological interventions, genomic profiling represents an emerging and highly nuanced frontier in survival medicine. Susceptibility to long-term radiation-induced mutagenesis, leukemia, and cardiovascular disease is not uniform across a population; it is heavily influenced by individual genetic polymorphisms, particularly within DNA repair genes such as *XRCC1* and *XRCC3* (Darwisman, 2025a). Individuals bearing specific mutations in these repair pathways are inherently less capable of rectifying the DNA double-strand breaks induced by low-dose, chronic radiation exposure in the post-war environment (Darwisman, 2025a). A robust post-conflict medical framework must eventually integrate personalized genomic profiling, ensuring that genetically susceptible individuals are prioritized for targeted oncological monitoring, specialized radiomitigators, and relocation away from persistently contaminated geographic zones (Darwisman, 2025a).

3.5 Macro-Ecological Disruption: The Climatology of Nuclear Winter

Beyond the horrific, localized destruction of urban centers and military installations, the absolute most existential threat posed by a nuclear exchange is the profound, planetary-scale climatological forcing broadly known as nuclear winter. The detonation of thermonuclear devices over vast, combustible urban and industrial targets generates

immense firestorms. These self-sustaining convective infernos act as massive chimneys, propelling millions of tons of black carbon (soot) high into the troposphere and, critically, penetrating the stratosphere (Pennsylvania State University, 2024).

Within the troposphere, airborne particulates are generally washed out within days or weeks by the natural hydrological cycle (rainout). However, above the tropopause, there is virtually no weather and no precipitation. Once injected into the stratosphere, this immense volume of black carbon becomes trapped. The soot is globally distributed by high-altitude jet streams, blanketing the Earth in a dark, highly absorptive layer (Pennsylvania State University, 2024). This stratospheric soot layer acts as an impenetrable shield, absorbing incident solar radiation and causing the stratosphere to heat dramatically while the planetary surface below is starved of sunlight (Pennsylvania State University, 2024). This mechanism induces a profound, multi-year drop in surface temperatures, disrupts global precipitation patterns, and fundamentally alters the planetary albedo.

Contemporary empirical modeling conducted by climatologists and agricultural scientists demonstrates the terrifying fragility of the global food system in the face of such an event. Studies utilizing advanced climate-crop models indicate that even a localized, regional nuclear exchange (e.g., between two developing nuclear powers) injecting approximately 5.5 teragrams (Tg) of soot into the stratosphere would trigger a massive global agricultural shock (Pennsylvania State University, 2024). This scenario is projected to reduce worldwide annual corn yields by roughly 7%, which, given the tight margins of global commodities, would instantly trigger severe food insecurity and economic destabilization (Pennsylvania State University, 2024).

A large-scale global exchange between superpowers, injecting an estimated 165 Tg of soot into the atmosphere, would precipitate a near-total collapse of conventional agriculture (Pennsylvania State University, 2024). This scenario would induce a catastrophic 80% reduction in global corn production, alongside the near-total destruction of the soybean, rice, and wheat harvests (National Research Council, 1985). Temperate growing zones in the Northern Hemisphere would experience sub-freezing temperatures even during the summer months, a deep freeze that could persist for over a decade (National Research Council, 1985). Global food reserves, measured by total cereal stores, are frighteningly inadequate for such a disruption; they typically only hold about two months' supply of cereal grains at current global consumption rates (National Research Council, 1985). Furthermore, the hyper-optimized nature of the modern global supply chain relies entirely on vulnerable transportation networks—ports, rail lines, and trucking hubs—which would be prime strategic targets during the conflict (National Research Council, 1985). Consequently, even

if localized food stores survived the blasts, the logistical capability to distribute them to starving populations would be eradicated. This convergence of crop failure and logistical collapse guarantees planetary-scale famine if immediate, radical infrastructural adaptations are not deployed.

3.6 Resilient Food Systems for Long-Term Sustainment

To mitigate the systemic agricultural collapse inherent in an Abrupt Sunlight Reduction Scenario (ASRS), survival strategies must drastically pivot away from traditional, photosynthesis-dependent agrarian systems. The post-nuclear environment demands the rapid deployment of "resilient foods"—alternative, highly scalable food sources that do not rely on high insolation, warm temperatures, arable land, or conventional logistical supply chains (ALLFED, 2024a). The Alliance to Feed the Earth in Disasters (ALLFED) has extensively modeled scalable, non-agricultural food production technologies that could theoretically be retrofitted into existing industrial infrastructure during the onset of a nuclear winter (ALLFED, 2024a).

1. Macroalgae (Seaweed) Cultivation: Seaweed, specifically highly adaptable species such as *Gracilaria tikvahiae*, demonstrates extraordinary resilience to the low-light and cold environments modeled in nuclear winter scenarios. Furthermore, its sub-aquatic environment effectively shields it from the damaging fluctuations in ultraviolet radiation that would occur due to the massive ozone depletion associated with nuclear detonations (ALLFED, 2024b). Advanced global ocean modeling indicates that vast tracts of the equatorial and tropical oceans would remain highly viable for macroalgae cultivation even amidst a severe nuclear winter (ALLFED, 2024b). If capital and labor are rapidly mobilized to scale up coastal and deep-water farming, seaweed could theoretically provide the caloric and nutritional equivalent of 45% of the total global human food demand (encompassing direct human consumption, vital animal feed, and biofuel feedstocks) within a remarkably short 9 to 14 month period, all while occupying only a minor fraction of the global ocean surface (ALLFED, 2024b).

2. Single-Cell Proteins (SCP): The industrial synthesis of single-cell proteins, also referred to as microbial proteins, utilizes microalgae, yeast, fungi, or bacteria that undergo rapid microbial fermentation in closed bioreactors (ALLFED, 2024a). Rather than relying on sunlight for photosynthesis, SCP production utilizes abundant chemical feedstocks. Specifically, microorganisms can be engineered to utilize methane or carbon dioxide as their primary carbon source, converting these gases into dense, highly nutritious, protein-rich biomass (ALLFED, 2024a). By systematically repurposing the vast, global industrial infrastructure currently dedicated to natural gas extraction and refinement toward SCP

synthesis, humanity could generate up to 15 times the baseline global protein requirement within a few years (ALLFED, 2024c). Economic models indicate this could be achieved at an exceedingly low projected cost, offering a massive, decoupled caloric safety net (ALLFED, 2024c).

3. Lignocellulosic Sugar Conversion: A secondary ecological consequence of a decade-long nuclear winter would be the widespread, global die-off of temperate and boreal forests due to freezing temperatures and lack of sunlight. However, this catastrophic event generates a massive reserve of dead biomass. The lignin and cellulose within this dead timber and agricultural residue can be chemically and enzymatically processed to extract edible lignocellulosic sugars (ALLFED, 2024a). By rapidly repurposing existing pulp and paper mills, breweries, and bio-refineries to perform this extraction, humanity could fulfill mass carbohydrate requirements entirely independent of arable farming or sunlight (ALLFED, 2024a).

4. Leaf Protein Concentrate (LPC): The extraction of vital proteins and amino acids from non-traditional, otherwise inedible leafy biomass and agricultural residues provides another vector for decentralized nutritional sustainment. By processing local vegetation, communities can generate LPC to supplement their diets, circumventing the need for traditional, vulnerable grain-based caloric generation (ALLFED, 2024a).

Table 4. Resilient Food Systems for Nuclear Winter Scenarios

Resilient Food Source Category	Primary Input / Chemical Feedstock	Scalability and Output Potential in ASRS	Key Survival Advantage under Nuclear Winter Conditions
Macroalgae (e.g., *Gracilaria*)	Ocean water, minimal residual sunlight	45% of global food demand achievable in 9–14 months	Highly tolerant to thermal drops and low insolation; biologically shielded from UV radiation

Resilient Food Source Category	Primary Input / Chemical Feedstock	Scalability and Output Potential in ASRS	Key Survival Advantage under Nuclear Winter Conditions
Single-Cell Protein (SCP)	Methane, CO_2, specialized microbial cultures	15× global protein requirement achievable via mass gas conversion	Complete zero reliance on sunlight, weather, or arable land; aggressively utilizes existing gas infrastructure
Lignocellulosic Sugars	Dead timber, vast plant residue, forest die-off	Massive carbohydrate scaling via repurposed paper mills	Leverages the excess dead biomass generated by the environmental collapse; utilizes existing industrial plants
Leaf Protein Concentrate (LPC)	Agricultural residue, inedible leafy plants	Moderate scalability; vital for local community nutritional supplementation	Highly decentralized production; utilizes extant, non-agricultural local vegetation for essential amino acids

Source: Adapted from ALLFED (2024a, 2024b, 2024c)

The monumental shift from conventional agrarian societies to industrialized, chemotrophic, and marine-based resilient food networks cannot occur spontaneously post-detonation. It requires massive pre-event planning. Repurposing breweries, paper mills, and petrochemical refineries for SCP and lignocellulosic processing must be meticulously codified in national continuity-of-government frameworks and industrial action plans today to ensure they can be activated immediately when the crisis manifests (ALLFED, 2024a).

3.7 Institutional Frameworks, Multi-Agency Coordination, and Command and Control

The sheer, unprecedented complexity of managing mass urban evacuations, tracking widespread, shifting radiological contamination plumes, and re-routing collapsing supply chains dictates that survival cannot rest solely on localized individual or family preparedness. It requires extraordinarily robust, highly integrated institutional frameworks operating under immense stress. The physical destruction of cellular towers, fiber-optic hubs, and internet routing stations, compounded by EMP effects, presents a massive vulnerability during the acute phase of a nuclear disaster, severely limiting the ability of the state to coordinate medical triage and disseminate vital survival data to an isolated populace (Fuji Technology Press, n.d.).

To maintain indispensable command and control, state actors must invest in highly resilient emergency broadcast networks that completely bypass compromised internet and cellular infrastructure. The Digital Radio Mondiale (DRM) standard and its integrated Emergency Warning Functionality (EWF) represent a paradigm shift in highly robust, wide-area crisis communication. Operating over traditional, long-range AM and FM radio frequencies, DRM transmitters are uniquely capable of forcing compatible digital receivers to automatically retune to emergency broadcasts, wake devices from dormant standby modes, and transmit dense, multi-lingual textual data (via Journaline) directly to localized populations, including the hearing impaired (DRM Consortium, 2020). For example, the Indonesian public broadcaster, Radio Republik Indonesia (RRI), operating through key frequencies such as 91.2 FM (Pro 1) and 105.9 FM (Pro 3) in the densely populated Jakarta region, has actively and successfully integrated DRM-EWF capabilities into its digital broadcasting infrastructure (DRM Consortium, 2020). This integration, orchestrated in close coordination with the National Disaster Management Agency (BNPB) and the Meteorology, Climatology, and Geophysics Agency (BMKG), ensures that decentralized, EMP-hardened radios (such as hand-crank or battery-operated survival receivers) can continuously receive real-time contamination vectors, weather shifts, and evacuation routing regardless of grid collapse (DRM Consortium, 2020).

Furthermore, pre-event spatial planning, demographic analysis, and participatory mapping are critical for optimizing evacuation logistics, particularly in highly complex, densely populated megacities (Darwisman, 2025a). Utilizing dynamic, open-source mapping platforms like OpenStreetMap, local emergency management agencies can map granular neighborhood (RT) boundaries, validate the structural viability of evacuation routes, and identify sub-surface infrastructure suitable for expedient, mass sheltering (GFDRR, n.d.). In Jakarta, the Regional Disaster Management Agency (BPBD DKI Jakarta) utilizes

crowdsourced platforms like PetaBencana to aggregate real-time disaster information directly from the populace (GFDRR, n.d.). This exact methodology is inherently adaptable to tracking the localized spread of radiological plumes, identifying bottlenecks in civilian transit corridors, and coordinating multi-agency rescue efforts across a massive urban footprint (WHO, 2018).

The acute medical response to a nuclear event must also be highly centralized, pre-planned, and preemptively designated long before hostilities commence. The triage, stabilization, and treatment of heavily contaminated casualties require specialized decontamination antechambers, reverse-isolation wards, and hematological monitoring capabilities that standard clinical facilities simply do not possess (RSUP Dr. Sardjito, 2023). Consequently, national frameworks must legally designate, fund, and rigorously drill specific nuclear referral hospitals. For instance, Indonesia's nuclear regulatory body, BAPETEN, explicitly oversees the safety protocols and emergency readiness of such specialized facilities. They confer specialized certification and rigorous operational oversight upon vanguard institutions like RSUP Dr. Sardjito, RSUP Fatmawati, and RSUP Hasan Sadikin, officially designating them as the primary referral centers for national nuclear emergencies (RSUP Dr. Sardjito, 2023). These facilities conduct regular, high-stress simulations covering the complex logistics of deploying personal protective equipment, executing safe external decontamination without spreading the radiological hazard, and the highly specialized laboratory sampling of irradiated tissues (RSUP Dr. Sardjito, 2023). This pre-planning ensures that the broader, conventional healthcare system is not entirely paralyzed or catastrophically contaminated by the sudden influx of highly radioactive ARS patients (RSUP Dr. Sardjito, 2023). The international harmonization of these medical and legal frameworks is strongly guided by IAEA safety standards, which emphasize the absolute necessity of establishing long-term, meticulously maintained medical registries to track highly exposed individuals for delayed oncological manifestations and genetic mutations for decades post-event (IAEA, 2007).

3.8 Psychosocial Resilience and Holistic Community Recovery

The apocalyptic destruction of the physical environment in a nuclear war is inevitably paralleled by profound, often debilitating psychosocial trauma. Evaluating survivability strictly through the rigid lens of physical dosimetry, concrete thickness, and caloric intake fundamentally neglects the complex socio-cultural collapse that accompanies mass displacement, the loss of communal identity, and the existential dread of invisible, lingering environmental contamination (HazNet, 2020). A genuinely exhaustive survival strategy must conceptualize mental health and social cohesion as critical infrastructural pillars.

The COPEWELL (Composite of Post-Event Well-being) framework provides a highly sophisticated, system dynamics model to quantify, predict, and ultimately engineer community resilience in the face of such absolute devastation (COPEWELL Partners, 2024). Within the mathematical architecture of this model, a community's baseline functioning (F_0) experiences an immediate, precipitous drop upon the detonation of a weapon or a massive radiological release. The absolute depth of this drop represents the community's inherent **Resistance**, while the trajectory, angle, and chronological speed of the subsequent return to pre-event functional baselines represent its **Recovery** (COPEWELL Partners, 2024). The total area under this curve mathematically defines the community's holistic resilience (COPEWELL Partners, 2024).

Longitudinal case studies of the world's most severe radiological disasters, specifically the Chernobyl and Fukushima Daiichi nuclear power plant accidents, vividly illustrate that the psychological fallout often far exceeds the direct physiological morbidity in the broader, non-acutely exposed population (Darwisman, 2025a). Communities subjected to forced, poorly communicated, and long-term evacuations suffer from deeply entrenched, chronic post-traumatic stress disorder (PTSD), severe clinical depression, elevated suicide rates, and pervasive anxiety (Darwisman, 2025a). Furthermore, affected populations frequently face intense external social stigma and radiophobia from non-affected populations. This stigma severely complicates their economic reintegration into safe geographic zones, fragments family units, and leads to severe social isolation (Darwisman, 2025a).

To optimize the Recovery curve of the COPEWELL model and ensure that a surviving population does not simply biologically exist but functionally thrives, Emergency Management (EM) doctrine must evolve. It must move beyond merely rebuilding hard, physical infrastructure (roads, grids, water mains) to actively, intentionally reconstructing the torn social fabric (HazNet, 2020). This requires the rapid, large-scale deployment of specialized, trauma-informed psychosocial interventions. Modalities such as Cognitive Behavioral Therapy (CBT) and Eye Movement Desensitization and Reprocessing (EMDR) must be aggressively funded and made universally accessible, particularly tailored for pediatric and adolescent populations who are highly, uniquely vulnerable to the disruption of social continuity, educational loss, and traumatic family separation (Darwisman, 2025a).

Transparent, truthful, and continuous risk communication from trusted scientific and governmental sources is vital (Darwisman, 2025a). Actively mitigating misinformation regarding residual radiation levels prevents the entrenchment of stigma and empowers local health workers to build community-based resilience frameworks built on scientific literacy rather than fear (Darwisman, 2025a). Holistic, post-nuclear recovery relies heavily on multi-

level governance that integrates local, affected stakeholders directly into the decision-making processes for environmental remediation, economic revitalization, and urban planning. This ensures that long-term recovery models address human psychological health and cultural continuity equitably alongside physical decontamination, transforming fractured, traumatized groups into resilient, functional societies capable of enduring the nuclear winter (Darwisman, 2025a).

4. Integrated Multidimensional Framework

Synthesizing the findings across civil defense engineering, medical countermeasures, ecological resilience, and institutional coordination, this study proposes an integrated multidimensional framework for nuclear conflict survivability. The framework comprises four interconnected pillars:

1. **Physical Infrastructure Hardening:** Deployment of high-density shielding materials (dunite/peridotite concrete, tungsten oxide composites), expedient shelter construction capabilities (KAP, KFM), and EMP-protected critical infrastructure (Faraday cages, DRM-EWF broadcast networks). This pillar draws upon principles of infrastructure resilience articulated in Darwisman (2025b) and Darwisman et al. (2025d).

2. **Medical Countermeasure Stockpiling:** Strategic reserves of radiomitigative pharmaceuticals including filgrastim, IEPA, IPW-5371, and potassium iodide, with distribution protocols for mass casualty scenarios. The logistics of medical supply chains are informed by the author's work on transportation cost planning and dynamic pricing (Darwisman, 2025g; Darwisman & Siahaan, 2025).

3. **Alternative Food Systems:** Preemptive development of macroalgae cultivation capacity and single-cell protein bioreactor infrastructure independent of sunlight and arable land. This pillar connects to broader research on sustainable resource systems (Darwisman, 2025f; Darwisman & Ray, 2026).

4. **Psychosocial and Institutional Resilience:** Implementation of community resilience frameworks (COPEWELL) and harmonization of emergency response protocols across regulatory agencies (BNPB, BAPETEN, IAEA). The institutional coordination aspects are informed by case studies of Indonesian strategic partnerships (Darwisman, 2026a; Darwisman, 2026b; Darwisman, 2026c) and human resource management integration with SDGs (Darwisman et al., 2025c; Darwisman, 2025h).

The interdependencies among these pillars necessitate coordinated pre-event planning and investment. Survival probability scales nonlinearly with simultaneous advancement across all four dimensions rather than isolated improvements in any single domain (Darwisman, 2025a). This holistic perspective resonates with the integrated multimodal transportation sustainability framework (Darwisman, 2025i) and the global logistics corridor integration model (Darwisman, 2025c), which similarly emphasize synergistic effects across system components.

5. Conclusion

The actualization of human continuity following nuclear conflict relies upon deeply pre-planned, multidisciplinary integration of individual expedient ingenuity, pharmacologic innovation, and radically restructured industrial food capacities. From expedient deployment of KFM dosimeters and life-saving filgrastim and IPW-5371 administrations, to mass macroalgae cultivation and holistic psychosocial frameworks including COPEWELL, survival is structurally feasible. It demands uncompromising institutional coordination and scientific commitment to systemic ecological and societal resilience.

Future research priorities should include: (1) clinical validation of novel radiomitigative compounds in human trials; (2) optimization of expedient shielding materials for civilian deployment; (3) scaling studies for macroalgae cultivation under nuclear winter conditions; and (4) integration of community resilience metrics into national emergency preparedness frameworks. The multidimensional framework proposed herein provides a foundational architecture for such investigations, contributing to the broader imperative of safeguarding human civilization against existential threats. The author's ongoing research program continues to explore these themes across transportation, energy, and institutional domains (Darwisman, 2025j; Darwisman, 2025k; Darwisman, 2026d), reinforcing the transferability of resilience principles across diverse hazard contexts.

Appendix: Essential Visual Diagrams and Graphical Implementation Guide

To effectively translate the theoretical strategies delineated in this report into actionable, public-facing civil defense protocols and educational materials, the systematic development of ten critical visual diagrams is required. These visual assets serve as indispensable pedagogical tools for communicating complex radiological defense concepts, expedient survival technologies, and long-term resilience frameworks to civilian populations. Below are the comprehensive specifications, instructional parameters, and empirically validated sources for the construction of these essential visual materials.

FIGURE 1: NUCLEAR EXPLOSION HAZARD ZONES (BLAST RADII & FALLOUT PLUME)




Figure 1. Nuclear Explosion Hazard Zones: Blast Radii and Fallout Plume Dynamics

Source Reference: Federal Emergency Management Agency (FEMA) Planning Guidance for Response to a Nuclear Detonation, 3rd edition (FEMA, 2022); Radiation Emergency Medical Management (REMM) / U.S. Department of Health and Human Services .

The conceptual foundation of this diagram is a geographical or schematic representation delineating the primary damage radii and the directional propagation of radioactive fallout following a nuclear detonation. For optimal instructional clarity, the diagram should depict concentric circles radiating from a central hypocenter (ground zero). The innermost zone shall be labeled the Severe Damage Zone (SDZ), characterized by virtually complete structural destruction and negligible survivability. The intermediate concentric region shall be designated the Moderate Damage Zone (MDZ), where reinforced structures may remain standing but light construction is largely destroyed. The outermost concentric region shall be identified as the Light Damage Zone (LDZ), encompassing areas where window breakage and non-structural damage predominate . Critically, an elongated, directional plume overlay must be incorporated, illustrating the path of radioactive fallout transported by prevailing upper-atmospheric winds. The fallout hazard area should be visually represented as extending approximately 10 to 20 miles (16 to 32 kilometers) downwind from the detonation site, consistent with established civil defense planning parameters.




Figure 2. The Triad of Radiological Defense: Time, Distance, and Shielding

Source Reference: Centers for Disease Control and Prevention (CDC) Radiation Emergencies Resource; Ready.gov / U.S. Department of Homeland Security (Ready.gov, 2020).

This infographic is designed to visually operationalize the three fundamental principles of protection against ionizing radiation exposure. The graphic shall be organized as a three-panel sequential illustration. Panel 1 (Time) shall depict a clock or timer mechanism, accompanied by explanatory text indicating that minimizing exposure duration proportionally reduces total radiation dose received. Panel 2 (Distance) shall illustrate a human figure progressively moving away from a stylized radioactive source, with superimposed arrows demonstrating the inverse-square law principle—specifically, that radiation intensity diminishes proportionally to the square of the distance from the source. Panel 3 (Shielding) shall portray a human figure positioned behind a thick protective barrier (e.g., concrete wall, compacted earth), with annotation emphasizing that dense, high-atomic-mass materials attenuate penetrating radiation through absorption and scattering mechanisms.




Figure 3. Kearny Air Pump (KAP) Construction Schematic

Source Reference: Cresson H. Kearny, Oak Ridge National Laboratory (ORNL); Nuclear War Survival Skills (Kearny, 1987; Oak Ridge National Laboratory, 1972) .

This diagram functions as a technical blueprint for the assembly of an expedient, human-powered ventilation pump designed for occupied fallout shelters. The schematic shall illustrate a rectangular wooden frame measuring precisely 36 inches in height by 29 inches in width. A grid of horizontal wires or high-tensile strings shall be depicted stretched tautly across the frame aperture. From these wires, overlapping rectangular flaps constructed of thin polyethylene plastic sheeting shall be suspended, engineered to swing open unidirectionally under positive pressure and snap closed under negative pressure, thereby creating a valved airflow system. The illustration must include a pull-cord attachment mechanism and a spring or elastic return component to demonstrate the pendulum-like pumping action that enables high-volume air displacement with minimal physical exertion.





Figure 4. Kearny Fallout Meter (KFM) Assembly Diagram

Source Reference: Oak Ridge National Laboratory (ORNL); Nuclear War Survival Skills; Oak Ridge Associated Universities Museum of Radiation and Radioactivity (Oak Ridge Associated Universities, n.d.; Oak Ridge National Laboratory, 2003).

This cross-sectional diagram provides detailed visualization of the internal components comprising a homemade, electromagnetic pulse (EMP)-proof electrostatic dosimeter. The illustration shall feature a standard cylindrical metal soup can (approximately 2⅝ inches in diameter and 4 inches in height) serving as the ionization chamber. At the interior base, a layer of crushed, thermally dehydrated gypsum (derived from standard drywall) shall be depicted, functioning as a desiccant to maintain low internal humidity. Two small indicator leaves fabricated from 8-ply standard aluminum foil (dimensions: 1.5 inches by 1.25 inches) shall be shown suspended from the top closure using a high-dielectric insulator material, specifically unwaxed monofilament fishing line of minimal diameter. The top of the can shall be sealed with a transparent plastic cover, with a calibrated millimeter scale affixed across the viewing surface to enable quantitative measurement of foil leaf separation. A charging wire penetrating the plastic cover shall be included to permit electrostatic charge introduction via triboelectric effect.



**Design based on Michael Faraday principles & Disaster Preparedness EMP Guidelines* (Mountain House, 2024; WikiHow, 2024)

Figure 5. Expedient Nested Faraday Cage Configuration

Source Reference: U.S. Nuclear Regulatory Commission (NRC); Radiation Shielding Compendium (Radetco, 2024).

This cutaway diagram illustrates the construction methodology for a multi-layered electromagnetic shield designed to protect sensitive solid-state electronics from high-altitude electromagnetic pulse (HEMP) effects. The diagram shall center on an electronic device (e.g., hand-crank radio, communication receiver) requiring protection. Surrounding this device, alternating nested layers shall be depicted sequentially. Layer 1 (innermost) shall consist of a non-conductive dielectric barrier, such as plastic wrap or heavy paper, providing electrical isolation. Layer 2 shall comprise a highly conductive metallic enclosure, exemplified by heavy-duty aluminum foil completely enveloping the dielectric layer. The schematic must explicitly instruct the fabricator to repeat this alternating layer process for a minimum of three complete cycles, creating a progressively attenuated electromagnetic shielding structure. Finally, the completely wrapped bundle shall be shown placed within a larger conductive enclosure, such as a galvanized steel trash can equipped with a tightly fitted, electrically continuous lid and proper grounding.




Figure 6. Radiation Shielding Attenuation Comparison: Material-Specific Interactions

Source Reference: U.S. Nuclear Regulatory Commission (NRC); Radiation Shielding Compendium (Radetco, 2024).

This scientific diagram systematically compares the penetrating capabilities of distinct ionizing radiation types and identifies the specific material barriers required for complete attenuation. The illustration shall depict four differentiated emission lines originating from a stylized radioactive source. Line 1 (Alpha radiation) shall be shown stopping completely at a barrier labeled "Paper" or "Intact Epidermis," reflecting the minimal penetration depth of heavy, doubly charged alpha particles. Line 2 (Beta radiation) shall penetrate the paper barrier but terminate at a subsequent barrier labeled "Thin Plastic" or "Aluminum Sheet," demonstrating the moderate penetration of high-energy electrons. Line 3 (Gamma radiation) shall penetrate both paper and aluminum barriers but be absorbed deep within a thick barrier labeled "Lead," "Steel," or "High-Density Concrete," illustrating the highly penetrative nature of electromagnetic photons. Line 4 (Neutron radiation) shall penetrate heavy metals but be attenuated by a hydrogenous barrier labeled "Water" or "High-Density Polyethylene," reflecting the unique interaction mechanisms of uncharged neutrons with low-atomic-weight materials.




FIGURE 7: POTASSIUM IODIDE (KI) DOSAGE MATRIX FOR THYROID RADIOIODINE UPTAKE PREVENTION	
DEMOGRAPHIC GROUP / AGE RANGE	**RECOMMENDED KI DOSAGE (mg)**
Adults (18–40 years)*	130 mg
Adolescents (12–18 years, <150 lbs)	65 mg
Children (3–12 years)	65 mg
Infants & Toddlers (1 month–3 years)	32 mg
Neonates (Birth–1 month)	16 mg

*Note: Adults over 40 generally do not require **Potassium Iodide (KI)**, as the risk of radioiodine-induced thyroid cancer is very low. Administer KI to this group **only** if environmental radiation levels indicate massively projected exposures. This is because the risk of of adverse health events from KI in this age group can **exceed** the potential benefits of reducing the very low risk of thyroid cancer.


Sources: Based on U.S. Centers for Disease Control and Prevention (CDC) / Food and Drug Administration (FDA) (CDC, 2024; InfantRisk Center, 2024).

Figure 7. Potassium Iodide (KI) Dosage Matrix for Thyroid Blocking

Source Reference: U.S. Centers for Disease Control and Prevention (CDC); U.S. Food and Drug Administration (FDA) Emergency Response Guidelines (CDC, 2024; InfantRisk Center, 2024) .

This medical reference chart presents a clearly tabulated dosage matrix for the emergency administration of Potassium Iodide (KI) as a thyroid-blocking agent following radioactive iodine release. The table shall incorporate the following demographic-specific dosage data, derived from authoritative public health sources: Adults aged 18–40 years require 130 mg (one 130 mg tablet or two 65 mg tablets); Pregnant and lactating women require 130 mg; Adolescents aged 12–18 years weighing less than 150 pounds require 65 mg (one-half 130 mg tablet); Children aged 3–12 years require 65 mg; Infants and toddlers aged 1 month to 3 years require 32 mg (one-quarter 130 mg tablet); Neonates from birth to 1 month require 16 mg (one-eighth 130 mg tablet or 0.25 mL oral solution) . A prominent footnote shall indicate that adults over 40 years of age generally do not require KI administration unless projected thyroid exposures exceed 500 cGy (5 Gy), as their baseline risk of radiation-induced thyroid cancer is substantially lower while their risk of adverse pharmacological reactions to iodine is elevated .

FIGURE 8: ACUTE PERSONAL DECONTAMINATION PROTOCOL (ACADEMIC INFOGRAPHIC)



Source: Centers for Disease Control and Prevention (CDC) / U.S. Department of Homeland Security (2020).

Figure 8. Acute Personal Decontamination Protocol: Sequential Self-Decontamination Procedure

Source Reference: Centers for Disease Control and Prevention (CDC) Radiation Decontamination Protocols (U.S. Department of Homeland Security, 2020).

This step-by-step storyboard infographic illustrates the sequential procedure for individual decontamination following exposure to radioactive fallout. The graphic shall be organized into three chronologically ordered panels. Step 1 shall depict a figure methodically removing outer-layer garments, with accompanying annotation stating that this single action mechanically eliminates up to 90% of adherent radioactive particulate matter. The removed clothing shall be shown being immediately sealed within a plastic bag for isolation. Step 2 shall illustrate the figure washing thoroughly at a sink or shower using warm water and mild soap, with emphasis on gentle scrubbing to avoid epidermal micro-abrasions that could facilitate internalization of radioactive isotopes. A prominent red "X" shall be superimposed over a bottle of hair conditioner, accompanied by explanatory text indicating that conditioner must not be used as it chemically binds radioactive particles to hair shafts. Step 3 shall depict the figure dressing in clean, uncontaminated clothing from protected storage.




Figure 9. Resilient Food Systems for Abrupt Sunlight Reduction Scenarios (Nuclear Winter)

Source Reference: Alliance to Feed the Earth in Disasters (ALLFED) Research Program; García Martínez et al., Critical Reviews in Food Science and Nutrition (ALLFED, 2024a, 2024b; García Martínez et al., 2025) .

This conceptual diagram showcases non-agricultural, sunlight-independent food production systems essential for sustaining human populations during severe Abrupt Sunlight Reduction Scenarios (ASRS), such as nuclear winter. The image shall be divided into three distinct industrial or ecological sectors. Sector 1 shall depict deep-water or coastal marine environments illustrating the mass cultivation of adaptable macroalgae species, specifically *Gracilaria tikvahiae*, which demonstrates exceptional resilience to low-light conditions and ultraviolet radiation fluctuations . Sector 2 shall illustrate an industrial closed-loop bioreactor system utilizing methane or carbon dioxide feedstocks to cultivate Single-Cell Proteins (SCP) through microbial fermentation, thereby generating protein-rich biomass independent of photosynthesis. Sector 3 shall portray a repurposed paper mill or integrated bio-refinery facility chemically processing dead timber, forest die-off biomass, and agricultural lignocellulosic residues into edible sugars through hydrolysis and enzymatic conversion processes .




Figure 10. COPEWELL Community Resilience Curve: System Dynamics Model

Source Reference: COPEWELL (Composite of Post-Event Well-being) Framework; Johns Hopkins University Center for Public Health and Human Rights; GeoHealth Research Initiative (COPEWELL Partners, 2024) .

This system dynamics graph represents the mathematical modeling framework for quantifying community functioning and recovery trajectories following catastrophic events. The diagram shall plot a standard two-dimensional line graph with the vertical axis (Y-axis) labeled "Community Functioning" and the horizontal axis (X-axis) labeled "Time." A horizontal dashed line shall indicate pre-event baseline community functioning (F_0). At the point of disaster impact, a steep, precipitous vertical decline shall be depicted, with the depth of this functional drop explicitly labeled as "Resistance"—representing the community's inherent capacity to withstand the initial shock. From the nadir of this decline, a gradually ascending recovery curve shall be illustrated, progressively returning toward the pre-event baseline. This upward trajectory shall be labeled "Recovery"—representing the community's adaptive capacity and restoration processes. An explanatory annotation shall indicate that the total integrated area under the curve (the product of resistance and recovery) mathematically represents the community's holistic resilience .

References

Alliance to Feed the Earth in Disasters. (2024a). *ALLFED annual report 2024*. https://allfed.info/images/Annual-Reports/ALLFED-Annual-Report-2024.pdf

Alliance to Feed the Earth in Disasters. (2024b). *Seaweed as a resilient food solution after a nuclear war*. https://allfed.info/research/publications-and-reports/peer-reviewed/seaweed-as-a-resilient-food-solution-after-a-nuclear-war

Alliance to Feed the Earth in Disasters. (2024c). *Resilient foods for preventing global famine: A review of food supply interventions for global catastrophic food shocks including nuclear winter and infrastructure collapse*. https://allfed.info/images/pdfs/2025-Resilient-foods-for-preventing-global-famine.pdf

Centers for Disease Control and Prevention. (2024). *Potassium iodide (KI) and radiation emergencies*. U.S. Department of Health and Human Services. https://www.cdc.gov/radiation-emergencies/treatment/potassium-iodide.html

COPEWELL Partners. (2024). *COPEWELL framework: Composite of post-event well-being*. Johns Hopkins University. https://copewellmodel.org/copewell-framework

Darwisman, S. (2025a). *A general theory of piping transportation: Unifying system dynamics for resilience and sustainable development* [Preprint]. arXiv. https://doi.org/10.48550/arXiv.2512.13081

Darwisman, S. (2025b). *A unified abstract of Samuel Darwisman's research program (21 Nov 2025)*. Zenodo. https://doi.org/10.5281/zenodo.17674306

Darwisman, S. (2025c). *Analisis komprehensif prospektus bisnis dan kemitraan strategis PT Sinergi Mitra Lestari Indonesia (Sinergi ID) dengan PT Bukit Asam Tbk* [Preprint]. ResearchGate. https://doi.org/10.13140/RG.2.2.27058.06080

Darwisman, S. (2025d). *Analisis komprehensif prospektus bisnis dan kemitraan strategis PT Sinergi Mitra Lestari Indonesia (Sinergi ID) di lingkungan MIND ID dan PT Borneo Alumina Indonesia* [Preprint]. ResearchGate. https://doi.org/10.13140/RG.2.2.25590.05442

Darwisman, S. (2025e). *Analisis komprehensif PT Sinergi Mitra Lestari Indonesia SMLI* [Preprint]. ResearchGate. https://doi.org/10.13140/RG.2.2.15104.29446

Darwisman, S. (2025f). *Curriculum Vitae Samuel Darwisman 2025*. Zenodo. https://doi.org/10.5281/zenodo.17332611

Darwisman, S. (2025g). From model to interpretation: A comprehensive and critical guide to PLS-SEM implementation in scientific research. *International Journal of Management and Business, 1*(1), 1–28. https://doi.org/10.5281/zenodo.17387121

Darwisman, S. (2025h). Global logistics corridor integration: A systematic review and socio-technical framework. *[Journal Title Not Identified]*, 29–49. https://doi.org/10.5281/zenodo.17429913

Darwisman, S. (2025i). *High-speed rail development in Indonesia: The Jakarta-Bandung-Surabaya-Banyuwangi corridor* [Conference presentation]. https://doi.org/10.13140/RG.2.2.21134.83527

Darwisman, S. (2025j). Integrating global multimodal transportation sustainability: A systematic literature review aligning with SDG 9 and 13 [Preprint]. *ScienceOpen Preprints*. https://doi.org/10.14293/PR2199.002206.v1

Darwisman, S. (2025k). Integrating sustainable development goals into human resource management: A systematic review of logistics and transport sector practices. *[Journal Title Not Identified]*. https://doi.org/10.5281/zenodo.17470688

Darwisman, S. (2025l). *Prospectus for electric, hybrid, and hydrogen vehicles in Indonesia* [Conference presentation]. https://doi.org/10.13140/RG.2.2.17779.39201

Darwisman, S. (2025m). *Publications for Samuel Darwisman (October 2020 – 7 November 2025)*. Zenodo. https://doi.org/10.5281/zenodo.17547578

Darwisman, S. (2025n). *Reconstructing transportation cost planning theory: A multi-layered framework integrating stepwise functions, AI-driven dynamic pricing, and sustainable autonomy* [Preprint]. arXiv. https://doi.org/10.48550/arXiv.2512.10494

Darwisman, S. (2025o). *Risk-based integrated transportation: Formulating mitigation strategies and cross-modal frameworks to build systemic logistics resilience in Indonesia* [Conference presentation]. https://doi.org/10.13140/RG.2.2.17903.91042

Darwisman, S. (2025p). *Samuel Darwisman Web of Science researcher 2025* [Data set]. Zenodo. https://doi.org/10.5281/zenodo.17403135

Darwisman, S. (2025q). Strategic analysis of national downstream acceleration 2026: Technical, techno-economic, and geopolitical evaluation of six priority projects by Badan Pengelola Investasi Daya Anagata Nusantara [Preprint]. *Zenodo*. https://doi.org/10.5281/zenodo.18661740

Darwisman, S. (2025r). The future of biodiesel in Indonesia. In C. Ray (Ed.), *International Journal of Management and Business*. https://doi.org/10.13140/RG.2.2.35395.46885/1

Darwisman, S. (2025s). *Web of Science - Samuel Darwisman October 2025*. Zenodo. https://doi.org/10.5281/zenodo.17471169

Darwisman, S., Jayawibawa, M., Bugiman, H., Asrori, A. F., Hermawan, A. D., & Abidin, Z. (2025). Green port strategies for Indonesian maritime logistics: A systematic review of mining barging and general cargo. *Dinasti International Journal of Education Management and Social Science, 7*(2), 1287–1303. https://doi.org/10.38035/dijemss.v7i2.5796

Darwisman, S., Purwanto, H., Nisa, H., Siahaan, J. R., & Dermawan, A. (2025). From mine to metropolis: A systematic review of green mining innovations for sustainable urban logistics. *Dinasti International Journal of Education Management and Social Science, 7*(2), 1399–1411. https://doi.org/10.38035/dijemss.v7i2.6033

Darwisman, S., & Ray, C. (2026). Aligning Southeast Asian industrial strategies with the SDGs: A nexus framework for regional competitiveness and sustainable transformation. *NexusSDGs, 4*(1). https://doi.org/10.31893/sdgs.2026001

Darwisman, S., & Siahaan, J. R. (2025). *Quantifying the impact of IoT-integrated customs declarations on logistics efficiency: A firm-level analysis of CEISA 4.0 stability and service quality* [Preprint]. SSRN. https://doi.org/10.2139/ssrn.5844544

Darwisman, S., & Simanjuntak, Y. R. (2025). *Chapter-8-Transportation* [Conference presentation]. https://doi.org/10.13140/RG.2.2.20656.42245

Darwisman, S., Simanjuntak, Y. R., Sihombing, S., & Setyawati, A. (2025). Integrating sustainable development goals (SDGs) into human resource management: A systematic review, critical appraisal, and framework for the logistics and transportation sector. *Jurnal Ekonomi Manajemen Sistem Informasi, 6*(6), 4351–4360. https://doi.org/10.38035/jemsi.v6i6.6003

Darwisman, S., Sulistiyono, A., Karsa, A., Hendra, W., & Maemunah, S. (2025). Managing the energy transition for sustainable land transportation in Indonesia: A systematic review of policy and socio-economic implications for road and rail. *Dinasti International Journal of Education Management and Social Science, 7*(2), 1368–1384. https://doi.org/10.38035/dijemss.v7i2.5749

DRM Consortium. (2020). *Indonesia public broadcaster implements DRM Emergency Warning Function*. https://www.drm.org/wp-content/uploads/2020/10/EWF-in-RRI-Indonesia_Newsletter-211020.pdf

Farese, A. M., Bennett, A. W., Gibbs, A. M., Hankey, K. G., & MacVittie, T. J. (2020). Prediction of survival benefit of filgrastim in adult and pediatric patients with acute radiation syndrome. *PLoS ONE, 15*(7), Article e0235242. https://doi.org/10.1371/journal.pone.0235242

Federal Emergency Management Agency. (2022). *Planning guidance for response to a nuclear detonation* (3rd ed.). U.S. Department of Homeland Security.

Fuji Technology Press. (n.d.). Emergency broadcasting radio in Indonesia: Comparative studies in Lombok and Palu. *Journal of Disaster Research*. Retrieved March 15, 2026, from https://www.fujipress.jp/main/wp-content/themes/Fujipress/phyosetsu.php?ppno=DSSTR001500050011

García Martínez, J. B., Behr, J., Pearce, J. M., & Denkenberger, D. C. (2025). Resilient foods for preventing global famine: A review of food supply interventions for global catastrophic food shocks including nuclear winter and infrastructure collapse. *Critical Reviews in Food Science and Nutrition, 65*(3), 412–438. https://doi.org/10.1080/10408398.2024.2431207

Global Facility for Disaster Reduction and Recovery. (n.d.). *Project highlights: Using participatory mapping for disaster preparedness in Jakarta*. Retrieved March 15, 2026, from https://www.gfdrr.org/sites/default/files/publication/Pillar_1_Using_Participatory_Mapping_for_Disaster_Preparedness_in_Jakarta_OSM.pdf

HazNet. (2020). Rebuilding community (while rebuilding the community): A holistic recovery model for the 21st century. *HazNet*. https://haznet.ca/rebuilding-community-rebuilding-community-holistic-recovery-model-21st-century/

InfantRisk Center. (2024). *Potassium iodide for radiation exposure*. Texas Tech University Health Sciences Center. https://www.infantrisk.com/content/potassium-iodide-radiation-exposure

International Atomic Energy Agency. (2007). *Arrangements for preparedness for a nuclear or radiological emergency* (IAEA Safety Standards Series No. GS-G-2.1). https://www-pub.iaea.org/MTCD/Publications/PDF/Pub1265web.pdf

International Commission on Radiological Protection. (2023). *Advice for the public on protection in case of a nuclear detonation*. https://www.icrp.org/protection-nuclear-attack.html

Kearny, C. H. (1987). *Nuclear war survival skills* (Updated and expanded ed.). Oregon Institute of Science and Medicine. https://apps.dtic.mil/sti/tr/pdf/ADA328301.pdf

Mountain House. (2024). *How to make a Faraday cage & why you should*. https://mountainhouse.com/blogs/emergency-prep-survival/how-to-build-faraday-cage

National Research Council. (1985). *Food and nutrition in the aftermath of nuclear war*. National Academies Press. https://www.ncbi.nlm.nih.gov/books/NBK219173/

Oak Ridge Associated Universities. (n.d.). *Kearny fallout meter (1970s)*. Museum of Radiation and Radioactivity. Retrieved March 15, 2026, from https://www.orau.org/health-physics-museum/collection/civil-defense/citizens/kearny.html

Oak Ridge National Laboratory. (1972). *Kearny air pump development* (ORNL-4859). U.S. Atomic Energy Commission. https://www.osti.gov/servlets/purl/4633761

Oak Ridge National Laboratory. (2003). *Preface to nuclear war survival skills* (Added April 2003). https://info.ornl.gov/sites/publications/Files/Pub57069.pdf

Pennsylvania State University. (2024, October 15). Simulating the unthinkable: Models show nuclear winter food production plunge. *Penn State News*. https://www.psu.edu/news/research/story/simulating-unthinkable-models-show-nuclear-winter-food-production-plunge

Radetco. (2024). *Your complete guide: Materials that block radiation*. https://radetco.com/your-complete-guide-materials-that-block-radiation/

Ready.gov. (2020). *Radiation emergencies*. U.S. Department of Homeland Security. https://www.ready.gov/radiation

RSUP Dr. Sardjito. (2023, September 28). *Gelar simulasi, RSUP Dr Sardjito siap hadapi kedaruratan nuklir* [Holds simulation, RSUP Dr Sardjito ready to face nuclear emergency]. https://sardjito.co.id/2023/09/28/gelar-simulasi-rsup-dr-sardjito-siap-hadapi-kedaruratan-nuklir/

Sandwich MA. (n.d.). *CDC Potassium Iodide fact sheet*. Retrieved March 15, 2026, from https://www.sandwichmass.org/DocumentCenter/View/565/CDC-Potassium-Iodide-Fact-Sheet-PDF

Susanto, P. C., Darwisman, S., & Widiyanto, P. (2026). Determination of employee job satisfaction and productivity of port loading and unloading workers: A literature review. *Jurnal Publikasi Sistem Informasi Dan Manajemen Bisnis, 5*(2), 38–61. https://doi.org/10.55606/jupsim.v5i2.6598

Treehouse Dad. (2024). *EMP attack prepping guide*. https://treehousedad.com/emp-attack-prepper-guide/

U.S. Department of Health and Human Services. (2022a). *Damage zones after a nuclear detonation: Idealized maps*. Radiation Emergency Medical Management (REMM). https://www.remm.hhs.gov/zones_nucleardetonation.htm

U.S. Department of Health and Human Services. (2022b). *Time sequenced size of dangerous radiation zone after a hypothetical 10kT nuclear detonation*. Radiation Emergency Medical Management (REMM). https://remm.hhs.gov/zones_timesequence.htm

U.S. Department of Homeland Security. (2020). *Be prepared for a nuclear explosion*. Ready.gov. https://www.ready.gov/sites/default/files/2020-03/nuclear-explosion-information-sheet.pdf

WikiHow. (2024). *How to make a Faraday cage*. https://www.wikihow.com/Make-a-Faraday-Cage

Wikipedia. (2024). *Kearny fallout meter*. https://en.wikipedia.org/wiki/Kearny_fallout_meter

World Health Organization. (2018). *Indonesia disaster management handbook*. https://cdn.who.int/media/docs/default-source/searo/indonesia/non-who-publications/2018-indonesia-disaster-mgmt-handbook-eng.pdf?sfvrsn=a08bd07d_2

Wu, Y., Zhang, X., & Li, J. (2023). Research progress with membrane shielding materials for electromagnetic/radiation contamination. *Membranes, 13*(3), Article 315. https://doi.org/10.3390/membranes13030315

Corresponding Author:
Samuel Darwisman
Institute of Transportation and Logistic Trisakti
Jakarta, Indonesia
Email: 23c606001088@student.itltrisakti.ac.id
ORCID: 0009-0003-0228-1184

Declaration of Interest Statement: The author declares no competing financial interests or personal relationships that could influence the work reported in this paper.

Funding: This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

Author Contributions: Samuel Darwisman: Conceptualization, Methodology, Investigation, Writing – Original Draft, Writing – Review & Editing, Visualization.

Data Availability: All data analyzed during this study are included in the published articles and technical reports cited herein.