

e-ISSN: 3048-6432

Volume 09 Issue 01
Jan-Apr 2026

***Corresponding Author :**

Mr. R. Mathesh
PG Scholar, ME.,
Environmental Engineering,
RVS Technical Campus,
Coimbatore, India

Submission Date: Dec 31,
2025

**Copyright Received
Date:** Feb 25, 2026

Recent Advances in Sustainable Biodiesel Production: Feedstocks, Catalysts, and Process Intensification

**Mr. R. Mathesh¹, Mr. P. Vignesh²,
Dr.D.Bhuvaneswari³, Dr. A. Kumar⁴, Sijin Seemon.C⁵,
Raghavan.S.⁶**

^{1,5,6}PG Scholar; ME., Environmental Engineering, RVS
Technical Campus, Coimbatore, India

^{2,3}Assistant Professor, Department of Civil Engineering,
RVS Technical Campus, Coimbatore, India

⁴Professor, Department of Civil Engineering, RVS
Technical Campus, Coimbatore, India

ABSTRACT

The growing demand for sustainable and low-carbon energy systems has intensified global research into biodiesel as a renewable alternative to petroleum-derived diesel. Biodiesel offers several advantages, including biodegradability, reduced greenhouse gas emissions, compatibility with existing diesel engines, and enhanced lubricity. However, conventional biodiesel production faces critical challenges such as high feedstock costs, competition with food resources, inefficient homogeneous catalysts, and energy-intensive processing conditions.

Recent research efforts (2023–2024) have focused on overcoming these limitations through the utilization of non-edible and second-generation feedstocks, heterogeneous catalysts derived from biomass and bio-waste, nanomaterial-based catalytic systems, and process intensification techniques such as ultrasound-assisted transesterification. This review consolidates and critically analyzes recent advancements in sustainable biodiesel production, with emphasis on *Jatropha curcas* and other non-edible oils, CaO-based and waste-derived catalysts, carbon-based nanomaterials, and ultrasonication technologies. The findings indicate significant improvements in reaction kinetics, catalyst reusability, energy efficiency, and environmental sustainability. Nonetheless, challenges related to catalyst leaching, long-term stability, scalability, and industrial commercialization persist. The review concludes by identifying research gaps and proposing future directions aligned with circular economy principles to facilitate large-scale, sustainable biodiesel production.

Keywords: Biodiesel, catalyst, feedstocks

INTRODUCTION

The rapid depletion of fossil fuel reserves, coupled with escalating environmental concerns such as climate change, air pollution, and greenhouse gas emissions, has accelerated the global transition toward renewable and sustainable energy sources. The transportation sector, which accounts for a significant share of global energy consumption and carbon emissions, urgently requires cleaner and renewable fuel alternatives. Biodiesel, derived from renewable biological lipid sources through transesterification or esterification reactions, has emerged as a promising substitute for conventional diesel fuel.

Biodiesel is characterized by several favorable properties, including renewability, biodegradability, low sulfur content, and reduced emissions of carbon monoxide (CO), particulate matter (PM), and unburned hydrocarbons. Despite these advantages, widespread commercialization of biodiesel remains constrained by economic and technical challenges. Conventional biodiesel production relies heavily on edible oils such as soybean, palm, and rapeseed oil, leading to food-versus-fuel conflicts and increased production costs. Additionally, homogeneous alkaline catalysts, though effective, suffer from drawbacks such as soap formation, wastewater generation, and difficulty in catalyst recovery.

To address these challenges, recent research has shifted toward sustainable production pathways involving non-edible feedstocks, heterogeneous and waste-derived catalysts, nanotechnology-based enhancements, and process intensification strategies. These approaches aim to reduce production costs, improve catalyst efficiency and reusability, minimize environmental impact, and enhance overall process sustainability. This review critically examines recent literature (2023–2024) to highlight technological progress,

identify existing limitations, and explore future opportunities in sustainable biodiesel production.

BIODIESEL PRODUCTION FUNDAMENTALS

Biodiesel is typically produced via transesterification of triglycerides present in oils or fats with short-chain alcohols (commonly methanol or ethanol) in the presence of a catalyst. The reaction yields fatty acid alkyl esters (biodiesel) and glycerol as a by-product. Key parameters influencing the process include feedstock quality, alcohol-to-oil molar ratio, catalyst type and concentration, reaction temperature, and mixing intensity.

Traditional homogeneous catalysts such as sodium hydroxide (NaOH) and potassium hydroxide (KOH) provide high conversion rates but are associated with several disadvantages, including sensitivity to free fatty acids (FFAs), soap formation, and complex downstream purification. Consequently, research efforts have increasingly focused on heterogeneous catalysts, which offer easier separation, reusability, and reduced environmental burden.

LITERATURE REVIEW

Ultrasound-Assisted Transesterification

Ultrasound-assisted transesterification has gained significant attention as an effective process intensification technique. Godlisten et al. (2024) conducted a comprehensive bibliometric analysis of ultrasonic transesterification research spanning two decades (2003–2023).[1] Their findings revealed a sharp increase in publications after 2007, particularly in developing economies where energy efficiency and cost reduction are critical.

Ultrasonication enhances cavitation phenomena, generating microbubbles that collapse violently, leading to localized high temperatures and pressures. This

effect significantly improves mass transfer between immiscible oil and alcohol phases, accelerates reaction kinetics, and reduces reaction time and catalyst loading. Compared to conventional mechanical stirring, ultrasonic processing can achieve higher biodiesel yields with lower energy consumption.

Despite its advantages, challenges remain in scaling up ultrasonic reactors for industrial applications. Energy efficiency at large scales, equipment cost, and reactor design optimization require further investigation.

Non-Edible Feedstocks

The use of non-edible feedstocks is a key strategy to address food-versus-fuel concerns. Joseph et al. (2024) reviewed *Jatropha curcas* oil as a second-generation biodiesel feedstock. *Jatropha* is a drought-resistant, non-edible plant that can be cultivated on marginal lands, making it an attractive sustainable option.[2]

The review highlighted favorable physicochemical properties of *Jatropha* oil, including suitable fatty acid composition and high cetane number. Engine performance studies demonstrated comparable efficiency to diesel fuel, with reduced emissions of CO, HC, and smoke opacity. Life cycle assessment (LCA) and cost analysis further supported the environmental and economic viability of *Jatropha*-based biodiesel.

However, challenges such as variable oil yield, high initial cultivation cost, and supply chain limitations must be addressed to ensure consistent large-scale production.

Carbon-Based Nanomaterials

Nanotechnology has introduced new possibilities for enhancing biodiesel production efficiency. Khan et al. (2024) explored the application of carbon-based nanomaterials, including graphene, carbon nanotubes (CNTs), and carbon nanofibers,

in biofuel synthesis. These materials offer high surface area, excellent thermal stability, and tunable surface chemistry.[3]

Carbon nanomaterials have been employed as catalyst supports, enzyme immobilization platforms, and active catalytic materials. Their incorporation improves catalytic activity, selectivity, and reusability. The study emphasized the potential of metal-free nanocatalysts and hybrid systems for greener biodiesel production.

Nevertheless, large-scale synthesis, cost, and environmental safety of nanomaterials remain critical concerns that require further research.

Bio-Waste Derived Catalysts

The development of catalysts from bio-waste materials aligns strongly with circular economy principles. Anil et al. (2024) reviewed heterogeneous catalysts derived from agricultural residues, food waste, shells, and ashes. Common sources include rice husk ash, banana peel ash, eggshells, and mollusk shells.[4]

These catalysts are rich in alkaline earth metal oxides such as CaO, MgO, and K₂O, which exhibit strong basicity and catalytic activity. Advantages include low cost, abundance, reduced waste disposal issues, and high reusability. The review emphasized their contribution to sustainable and decentralized biodiesel production.

However, catalyst variability, leaching of active sites, and inconsistent performance across feedstocks remain challenges.

CaO-Based Catalysts

CaO-based catalysts have emerged as one of the most extensively studied heterogeneous catalysts for biodiesel production. Siri et al. (2023) focused on CaO derived from natural waste sources

such as eggshells and snail shells. These materials exhibit high catalytic activity due to their strong basic nature and porous structure.[5]

The study reported high biodiesel yields under optimized conditions. However, CaO catalysts are susceptible to moisture and CO₂ poisoning, leading to reduced activity. Leaching of calcium ions into the reaction medium also affects long-term stability and biodiesel purity.

Surface modification, doping with other metal oxides, and catalyst encapsulation have been proposed as potential solutions.

Biomass Waste-Derived Solid Catalysts

Supongsena et al. (2024) reviewed solid acid and base catalysts derived from biomass waste, highlighting their industrial potential. These catalysts enable both esterification and transesterification reactions, making them suitable for high-FFA feedstocks.[6]

Despite promising laboratory-scale results, issues related to catalyst deactivation, regeneration efficiency, and scalability remain significant barriers to commercialization. The authors emphasized the need for pilot-scale studies and standardized preparation methods.

METHODOLOGY

This review adopts a systematic narrative review methodology, focusing on peer-reviewed journal articles published between 2023 and 2024. Databases such as Scopus, Web of Science, and ScienceDirect were consulted using keywords including sustainable biodiesel, ultrasound transesterification, bio-waste catalysts, CaO catalysts, and nanomaterials. Studies were analyzed based on feedstock type, catalyst source, reaction enhancement techniques, sustainability metrics, and scalability potential. Comparative evaluation was

conducted to identify trends, advantages, limitations, and research gaps.

RESULTS AND DISCUSSION

The reviewed literature demonstrates that sustainable biodiesel production is increasingly feasible through integrated technological approaches. Ultrasound-assisted transesterification significantly enhances reaction kinetics and reduces processing time. Non-edible feedstocks such as *Jatropha curcas* mitigate food security concerns while maintaining fuel quality. Waste-derived and CaO-based catalysts reduce production costs and environmental impact, while carbon nanomaterials further enhance catalytic efficiency and selectivity.

However, several challenges persist. Catalyst leaching and deactivation limit long-term usability. Nanomaterial-based systems face scalability and cost constraints. Industrial-scale implementation of ultrasonication requires optimized reactor design and energy analysis. Combining waste-derived catalysts with process intensification techniques appears particularly promising for future commercialization.

CONCLUSION AND FUTURE SCOPE

This review highlights substantial progress in sustainable biodiesel production through advancements in feedstocks, catalysts, and processing techniques. The integration of non-edible oils, bio-waste-derived heterogeneous catalysts, carbon nanomaterials, and ultrasound-assisted transesterification offers a viable pathway toward economically and environmentally sustainable biodiesel production.

Future research should focus on catalyst stabilization, long-term reusability, techno-economic and life cycle assessments, pilot-scale demonstrations, and policy-driven commercialization strategies. Emphasis on circular economy principles and waste

valorization will further strengthen biodiesel's role in the global renewable energy transition.

REFERENCES

1. Godlisten, A., et al. (2024). *Exploring the landscape of ultrasonic transesterification for biodiesel production.*
2. Joseph, B., et al. (2024). *Jatropha curcas oil: A potential feedstock for biodiesel.*
3. Khan, N. R., et al. (2024). *Carbon-based nanomaterials in biofuel synthesis.*
4. Anil, N., et al. (2024). *Bio-waste derived catalysts for biodiesel production.*
5. Siri, S., et al. (2023). *Advances in CaO-based catalysts for biodiesel synthesis.*
6. Supongsenla, P., et al. (2024). *Biomass waste-derived catalysts: Advances and challenges.*